

#### VARIANTS

6150FZ | Washbasin faucet, 6 V, Bluetooth

### 6150 FZ | VVASHBASIN FAUCET, 6 V,BLUETCOTH

# Oras Electra

EANCODE 6414150094132

**ACTIVE MARKET AREAS** 

INT, FIN, NOR, SWE, DNK, POL, EST, LTU, LVA, UKR





# Oras Electra

More than 30 years of experience in electronic faucets truly shows in Oras Electra, our most widely used and versatile touchless faucet family. Oras introduced the touchless faucets in the public premises already in the 1990s, and in the 21st century, the electronic faucets have rapidly become more common also in the household use. With touchless faucets, water consumption can be reduced by half, while user-friendliness and hygiene rise to a whole new level.

#### **Features**

#### Aerator

PCA® - constant ?ow rate regardless of pressure variations, Standard aerator

#### Connection

Flexible inlet pipes

#### Electronic parts

Autofocus infrared sensor, Solenoid valve, Low battery indicator

#### Lever/Handle

Temperature control handle

#### Mechanical parts

Mixing valve for manual temperature control, Non-return valve(s), Litter ?lter(s)

#### Special features

Software settings adjustable via App, Convertible for cold or premixed-water supply

#### Spout

Fixed spout, Casted construction	
Color	
Chrome	
Temperature	
Temperature preset ?xable	
Software settings	
Solivale Sellings	
After?ow period	
3s (1-20s)	
Automatic ?ush	
off (off/1-120h)	
Automotic Oral maried	
Automatic ?ush period	
30s(1-1800s)	
Max. ?ow period	
2 min (1 - 1800 s)	
Flow attributes	
Flow-rate at 300 kPa (with ?ow controller)	
0.10 l/s	
Pressure loss with ?ow (0.1 l/s)	
200 kPa	
Technical properties	
Connection size	
G3/8	
Hot water supply	
max. +70°C	
Material	
Brass	
Due in office.	
Projection	
96 mm	
Working pressure	
100 - 1000 kPa	

# Electronics

Battery Lithium 2CR56V

# Regulations

EMC Directive

2014/53/EU

Noise class

I (ISO 3822)

Protection class

IP55

# Approvals

GDV Danmark

04/00229

STF

EUFI-RTH-00031-11